

FREE FLAP 1.7

FOR MID-SIZED ONE PIECE FLAPS



Model	A	В	С
Cabinet height (mm)	Flap weight (kg)		
200	1.7 - 4.6	3.6 - 7.9	6.8 - 14.7
225	1.5 - 4.1	3.1 - 7.1	6.0 - 13.1
250	1.3 - 3.8	2.9 - 6.4	5.4 - 11.8
275	1.2 - 3.3	2.5 - 5.7	4.8 - 10.6
300	1.1 - 3.1	2.4 - 5.1	4.4 - 9.6
325	1.0 - 2.8	2.1 - 4.6	4.0 - 8.8
350	0.9 - 2.6	2.0 - 4.2	3.7 - 8.1
375	0.9 - 2.3	1.9 - 3.8	3.5 - 7.5
400	0.8 - 2.1	1.7 - 3.6	3.2 - 7.0
425	0.7 - 1.9	1.5 - 3.4	2.8 - 6.5
450	0.6 - 1.7	1.4 - 3.2	2.7 - 6.1

Material: Fitting: Steel

Cover cap: Plastic Fitting: Nickel plated,

> Finish/Colour: Fitting: Nickel plated, Cover cap: White, RAL 9003

For flap height: 200 - 450 mm

> Opening angle: 107° (can be limited to 90° by means of optional

opening angle restraint)

> Adjustment facility: Height/side/tilting angle of front ± 1.5 mm,

holding power

> Installation: Fitting for screw fixing with pre-mounted Euro

screws, front panel without tools (clip system

onto pre-mounted screw-on brackets)

Supplied with:

- > 2 Flap Stay fittings (left/right)
- > 2 Cover caps for fitting (left/right)
- > 2 Screw-on brackets for wooden flaps
- > 1 Set of installation instructions
- > 1 Drilling template
- > 1 Opening angle restraint

Model	Cat. No.
A	372.91.720
В	372.91.721
С	372.91.722

Opening angle restraint



> Area of application: For limiting opening angle of 107° to 90°

Material	Cat. No.
Plastic	372.91.499

FREE FLAP 3.15

FOR MID-SIZED ONE PIECE FLAPS



Model	D	E	F	G
Cabinet height (mm)	Flap weight	(kg)		
350	5.2 - 11.0	6.7 - 14.3	10.1 - 21.4	13.5 - 27.3
375	4.9 - 10.2	6.3 - 13.1	9.4 - 19.8	12.5 - 25.2
400	4.7 - 9.6	5.9 - 12.4	8.9 - 18.6	11.8 - 23.3
425	4.4 - 9.0	5.6 - 11.6	8.3 - 17.4	11.0 - 21.8
450	4.1 - 8.4	5.2 - 10.9	7.8 - 16.3	10.4 - 20.5
475	3.9 - 8.0	4.9 - 10.3	7.4 - 15.4	9.8 - 19.3
500	3.7 - 7.5	4.7 - 9.7	7.0 - 14.6	9.2 - 18.3
525	3.5 - 7.1	4.4 - 9.2	6.6 - 13.9	8.8 - 17.3
550	3.3 - 6.8	4.2 - 8.8	6.3 - 13.2	8.3 - 16.5
575	3.2 - 6.5	4.0 - 8.4	6.0 - 12.5	8.0 - 15.6
600	3.0 - 6.2	3.8 - 8.0	5.7 - 12.0	7.6 - 15.0
625	2.8 - 5.9	3.6 - 7.6	5.4 - 11.5	7.2 - 14.4
650	2.6 - 5.6	3.4 - 7.3	5.3 - 11.0	6.9 - 14.0

> Feature: Integrated opening angle restraint

Material: Fitting: Steel

Cover cap: Plastic Fitting: Nickel plated,

Cover cap: White, RAL 9003

> For flap height: 350 - 650 mm

> Opening angle: 90° or 107° (adjustable on fitting)

> Adjustment facility: Height/side/tilting angle of front ± 1.5 mm,

holding power

Installation: Fitting for screw fixing with pre-mounted Euro

screws, front panel without tools (clip system

onto pre-mounted screw-on brackets)

Supplied with:

Finish/Colour:

- > 2 Flap Stay fittings (left/right)
- > 2 Cover caps for fitting (left/right)
- > 2 Screw-on brackets for wooden flaps
- > 1 Set of installation instructions
- 1 Drilling template

Model	Cat. No.
D	372.91.730
E	372.91.731
F	372.91.732
G	372.91.733