

# 3WAY ADJUSTABLE CONCEALED HINGE



# HES3D-160







PAT.P

- 3 WAY adjustment function allows vertical, horizontal, and depth adjustment after hinge installed
- Easy installation / removal
- Supplied with stainless steel flat head screw
- Cover hides all screw heads for clean appearance
- Door weight: Max. 45kg (99lbs) / 2pcs
- Door Thickness: Min. 35mm (1-3/8")
- Max. Door Size: H 2000mm x W 900mm (H 78-47/64" x W 35-7/16")


Item No.	Finish / Color
HES3D-160SL	Matte Silver
HES3D-160GL	Matte Gold

Item No.	Weight (g)	Box (pcs)	Carton (pcs)
HES3D-160SL	700	2	20
HES3D-160GL			

No.	Part Name	Material	Finish / Color
①	Body	Zinc Alloy	Matte Silver Matte Gold
②	Base Frame	Zinc Alloy	
③	Arm	Aluminum	-
④	Shaft	304 Stainless Steel	-
⑤	Cover	ABS	Matte Silver, Matte Gold




Bore Dimensions




To determine the door and frame dimension, (G) must be taken into account.  
G = Min. 6mm + doorsill



HES3D-190SL




**a. Detailed View**



For Easy Installation

1. Separate parts as shown in picture "a".
2. Screw on the Hinge Body to door, and Hinge Bracket to door frame.
3. As shown in picture "b", insert Hinge Body straight into Hinge Bracket. Bracket will temporarily hold the Body for easy installation.
4. Use "screw A" to fix Body on Bracket.
5. Adjust horizontally by turning "screw B".
6. Loosen "screw A" for vertical adjustment. Tighten "screw A" after vertical adjustment completed.
7. For depth adjustment, loosen "screw C" (one turn). Tighten "screw C" after completed.
8. Snap on plastic covers after all above completed.

**b. Installation**



**c. 3WAY Adjustment**

